


# Main title 48/56pt

## Product/Model.

roger

### Title 18 pt – Rotis SansSerif bold

|                                     |                                                |
|-------------------------------------|------------------------------------------------|
| Dimensions (L x W x H)              | 101.3 x 76.1 x 49 mm (4 x 3 x 1.9 ")           |
| Weight                              | 90 g (3.1 oz)                                  |
| Color                               | Champaign                                      |
| Operating conditions                | 5° to +40° Celsius (41° to 104° Fahrenheit)    |
| Transport and storage conditions    | -20° to +60° Celsius (-4° to +140° Fahrenheit) |
| Humidity during transportation      | Up to 90% (non condensing)                     |
| Humidity during storage             | 0% to 70% (non condensing)                     |
| Humidity during operation           | 0% to 85% (non condensing)                     |
| Atmospheric pressure during use     | 800 hPa to 1500 hPa                            |
| Included Parts                      | Power supply                                   |
| micro-USB cable (for charging only) |                                                |
| Cleaning tool                       |                                                |
| External Interfaces                 | micro-USB port                                 |
| Battery                             | None                                           |
| Charging time                       | See Phonak Audéo M                             |



### Subtitle 11 pt – Rotis SansSerif bold

|                                  |                                                |
|----------------------------------|------------------------------------------------|
| Dimensions (L x W x H)           | 101.3 x 76.1 x 49 mm (4 x 3 x 1.9 ")           |
| Weight                           | 90 g (3.1 oz)                                  |
| Color                            | Champaign                                      |
| Operating conditions             | 5° to +40° Celsius (41° to 104° Fahrenheit)    |
| Transport and storage conditions | -20° to +60° Celsius (-4° to +140° Fahrenheit) |

Subtitle 11 pt – Rotis SansSerif bold

- Proven Roger speech-in-noise performance
- Fully automatic microphone mode selection
- Manual microphone mode option
- Advanced microphone beamforming
- 'Zoom into' soft voices in quiet and over distance
- Audio input for connection to multimedia devices
- Bluetooth for cell phone connection

Subtitle 11 pt – Rotis SansSerif bold

|                            |                                             |
|----------------------------|---------------------------------------------|
| Microphone characteristics | 101.3 x 76.1 x 49 mm (4 x 3 x 1.9 ")        |
| Microphone                 | 90 g (3.1 oz)                               |
| Array microphone           | Champaign                                   |
| Microphone modes           | 5° to +40° Celsius (41° to 104° Fahrenheit) |

Subtitle 11 pt – Rotis SansSerif bold

|                                                        |                            |
|--------------------------------------------------------|----------------------------|
| Roger characteristics                                  | Up to 90% (non condensing) |
| Transmission technology                                | 0% to 70% (non condensing) |
| 2.4 GHz including adaptive automatic frequency hopping | 0% to 70% (non condensing) |
| Power emission                                         | 0% to 85% (non condensing) |
| 32 mW                                                  | 800 hPa to 1500 hPa        |

Operating range

|                                                |                            |
|------------------------------------------------|----------------------------|
| 10 meters / 33 feet (typical)                  | 0% to 70% (non condensing) |
| 20 meters / 66 feet (ideal conditions)         | 0% to 70% (non condensing) |
| Roger system data (Connect)                    | micro-USB port             |
| Frequency (Roger microphone to Roger receiver) | None                       |
| 2.4 GHz                                        | See Phonak Audéo M         |

Connect operating range

|                              |                                                                                                                                        |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| 10 cm / 3.9 inches           | 0% to 70% (non condensing)                                                                                                             |
| Roger network                | 0% to 70% (non condensing)                                                                                                             |
| Compatible Roger receivers   | 0% to 70% (non condensing)                                                                                                             |
| All personal Roger receivers | 0% to 70% (non condensing)                                                                                                             |
| Number of Roger receivers    | 0% to 70% (non condensing)                                                                                                             |
| Unlimited                    | 0% to 70% (non condensing)                                                                                                             |
| Compatible Roger microphones | Roger Select, Roger Select iN, Roger Table Mic II, Roger Table Mic II iN, Roger Pen, Roger Pen iN, Roger EasyPen and Roger Clip-On Mic |
| Audio characteristics        |                                                                                                                                        |

Oxx-xxxx-xx/V100/2025-xx/xx © 2025 Sonova AG All rights reserved